



REQUEST FOR QUOTATION FOR THE PROCUREMENT OF GOODS AND SERVICES

<b>**Mandatory to fill in**</b>	
COMPANY NAME:	Quotation No. 23-10-819
CONTACT No.	Purchase Request No. G-2023-10-1138
Address:	Purpose: For Implementation of projects under program "Educational Robots for Innovative Educational Technology" of Advanced Robotics and Intelligent Control Center (ARICC) (12 months)
TIN No.	ABC: 38,225.00
PhilGEPS Registration No.	Please indicate days of delivery: _____ Calendar Days
EMAIL ADDRESS:	upon receipt of Purchase Order

INSTRUCTIONS TO SUPPLIERS:

1. Please quote your lowest price on the item/s listed below comprising the necessary taxes.
2. It is mandatory to indicate the brand and/or model of the items being offered and to attach a brochure thereof whenever applicable
3. Indicate the warranty period in cases of equipment or whenever applicable.
4. Forthwith submit the accomplished quotation duly signed by your representative.
5. Suppliers are required and mandated to attach and submit the following documentary requirements:  
a) Valid Mayor's/ Business Permit;    b) BIR Certificate of Registration;    c) Authority to Print Receipt;    and    d) PhilGEPS Membership Certificate    e) Omnibus Sworn Statement
6. All items must conform with the internationally accepted standard and sub-standard items shall not be accepted.

Pls. fill up this blank Space

ITEM NO.	ITEM & SPECIFICATION	QTY UNIT	BRAND & MODEL OFFERED	UNIT PRICE	TOTAL PRICE
	<b>PNEUMATICS</b>				
1	Suction Cup, 30mm 30mm PUR Suction Cup, VAS-30-1/8-PUR-B	6 pcs			
2	Pneumatic Hose, Outside Diameter: 6mm, Length = 50m Compressed Air Pipe Blue PE 6mm x 50m PEN Series, 551457 Hose Outside Diameter:6mm Hose Inside Diameter:4mm Colour: Blue Material: PE Length:50m Maximum Operating Pressure:10 bar Manufacturer Series: PEN Minimum Operating Temperature: -30°C Maximum Operating Temperature: +60°C Number of Tubes:1 Model Number p:551457	1 pc			
3	Pneumatic Hose, Outside Diameter: 8mm, Length = 50m Compressed Air Pipe Blue PE 8mm x 50m PEN Series, 551458 Hose Outside Diameter:8mm Hose Inside Diameter:5.7mm Colour: Blue Material: PE Length:50m Maximum Operating Pressure: 10 bar Manufacturer Series: PEN Minimum Operating Temperature: -30°C Maximum Operating Temperature: +60°C Model Number p:551458 Number of Tubes: 1	1 pc			
4	2/2, Closed, Monostable Solenoid Pilot Valve - Electrical Push In 6 mm MHJ Series 24V dc, 567503 Function:2/2, Closed, Monostable Connection Port Thread: Push In 6 mm Actuation Type: Electrical Manufacturer Series: MHJ Mounting Style: Through Hole Solenoid Voltage:24V dc Solenoid Fitted: Yes Number of Ports:2 Maximum Flow Rate:160L/min Solenoid Power Consumption:3.2W Minimum Operating Pressure:0.5bar Maximum Operating Pressure:6 bar Minimum Operating Temperature: -5°C Maximum Operating Temperature: +60°C Number of Positions: 2	1 pc			

5	1 L vacuum pump rotary micro vane vacuum pump, 3cfm Name: Rotary Vane Vacuum Pump Model: FY-1H-N (Mini 1L) Material: Aluminum Alloy Casing Rated voltage: 220V- / 50Hz Pumping rate: 3.6m3 / h Limit pressure: 2Pa Motor power: 150W Refueling amount: 150ml Dimensions: 255 x 105 x 202mm Weight: 4.2Kg Inlet connection thread: 7/16 "-20UNF	1 pc			
6	24L Industrial Air Compressor 2HP AC20248P Specifications: - Voltage: 220-240V-60Hz - Input power: 1.5 kW (2 HP) - Tank: 24L(6.3Gal) - Noise: 96db - 1000HR lifetime promise - Pump lubricated with oil - No-load speed: 2850rpm - Operation pressure: maximum 8bar (116psi) - Air displacement: 93L/min @40psi (2.7bar) - Applications of Air compressor - Operation of small engines - Pneumatic tools - Air hoists - Industrial cleaning by air blast - Tire inflation - Paint spraying	1 pc			
7	Pneumatic Reducer Pushin Fitting Straight Connector Air Tube, 8mm to 6mm - Operating Pressure: 0-150 PSI / 0-990 kpa - Pressure range: 0-0.9MPa(0-9.2kgf/cm2) - Operating Temperature: 0 - 60 °C - Plastic Body: PBT (Polybutylene terephthalate) - Metal Body: Nickel Plated Brass - Release Button: POM (Poly oxy methylene copolymer) - Grip Ring: Stainless Steel	26 pcs			
8	Pneumatic Reducer Pushin Fitting Straight Connector Air Tube, 10mm to 8mm - Operating Pressure: 0-150 PSI / 0-990 kpa - Pressure range: 0-0.9MPa(0-9.2kgf/cm2) - Operating Temperature: 0 - 60 °C - Plastic Body: PBT (Polybutylene terephthalate) - Metal Body: Nickel Plated Brass - Release Button: POM (Poly oxy methylene copolymer) - Grip Ring: Stainless Steel	25 pcs			
	<b>By Lot</b>				
	<b>NOTE: Please attach brochure and indicate days of delivery</b>				

Accomplished by:

By the authority of the University President.  

DR. CECILIA A. ZERONIMO  
BAC Chairperson

Supplier's Representative  
(Print name and Signature)

Canvassed by:

Date Accomplished :

Name and Signature

BulSU-OP-PU-03F3  
Revision: 1